

ZCKJ1

limit switch body ZCKJ - fixed - w/o display - 1NC
+1NO - snap action - Pg13



Main

| | |
|-------------------------------|--|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch body |
| Device short name | ZCKJ |
| Body type | Fixed |
| Product compatibility | XCKJ |
| Associated head | ZCKE619 ZCKE64 ZCKE629 ZCKE65 ZCKE63 ZCKE67 ZCKE06 ZCKE05 ZCKE21 ZCKE61 ZCKE08 ZCKE23 ZCKE66 ZCKE62 |
| Body material | Metal |
| Cable entry | 1 entry tapped for Pg 13.5 cable gland |
| Number of poles | 2 |
| Contacts type and composition | 1 NC + 1 NO |
| Contact operation | Snap action |
| Number of steps | 1 1 position |
| Contacts material | Silver plated contacts |

Complementary

| | |
|---------------|---------|
| Local display | Without |
|---------------|---------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

| | |
|--|---|
| Electrical connection | Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm ² |
| Positive opening | With |
| Minimum actuation speed | 0.01 m/min |
| [Ie] rated operational current | 3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A 0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 500 V (pollution degree 3) conforming to IEC 60947-1 for contact block 300 V conforming to CSA C22.2 No 14 for contact block 300 V conforming to UL 508 for contact block |
| Maximum resistance across terminals | 0.25 mOhm conforming to IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | IEC 60664 6 kV IEC 60947-1 6 kV |
| Short-circuit protection | 10 A cartridge fuse, type gG |
| Electrical durability | 5000000 cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Electrical circuit type | Indicator light module 2 neon lights AC, 110/120 V (95...130 V) service life: 20000 h |
| Width | 40 cm |
| Height | 81.5 cm |
| Depth | 44 cm |
| Net weight | 0.34 kg |
| Terminals description ISO n°1 | (11-12)NC (13-14)NO |

Environment

| | |
|---------------------------------------|--------------------------------------|
| IP degree of protection | IP66 |
| IK degree of protection | IK07 |
| Ambient air temperature for operation | -25...70 °C for standard environment |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.284 kg |
| Package 1 Height | 0.430 dm |
| Package 1 width | 0.880 dm |
| Package 1 Length | 0.450 dm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

ZCKJ1 is replaced by:



Industrial range ZCKJ1H29

limit switch body ZCKJ - fixed - w/o display - 1NC+1NO - snap action - M20

Qty 1

Reason for Substitution: Rebranding | Substitution date: 15 February 2006
